
# **N** Series


# ► 200DW | 200B | 200M Drawer Lock



ANSI/BHMA A156.11 Grade 1 E07041

Woodwork Institute (WI) acknowledged product





# 200DW

Function: Standard function lock Includes: 2 keys, 12-3 bar strike, and lock mounting screws

## 200B - Weather Resistant

Function: Weather resistant construction. Suitable for outdoor use in covered areas only. Includes: 2 keys, 12-3 bar strike, and lock mounting screws

## 200M - MRI Function

Function: MRI locks are made of all non-magnetic materials and components specifically for use in MRI medical applications.

Includes: 2 keys, 56-1 bar strike, and lock mounting screws (keys, components and materials are non-ferrous/non-magnetic)

## 200DW

Item	Function	Finish	Cyl. Length	Keying			
200DW	Drawer	26D, US4, 10B, US19	15/16" or 1-3/8"	KD, KA 101,103,107,915 KA 51001,51002,51003,51004* <sup>note</sup> Custom keyed			
200DW	Drawer	26D, 10B	1-5/8"				
Key-retaining:		Specify item <b>200KI</b> for inverted drawers and <b>200KV</b> for vertical drawers. ( <b>BKI</b> and <b>BKV</b> designations are <i>only required for key retaining locks</i> ).					
Long bolt:		Specify LB for long bolt installed in lock.					

#### 200B - B Series (Weather Resistant)

ltem	Function	Finish	Cyl. Length	Keying	
200B	Drawer	26D, US4, 10B, US19	15/16" or 1-3/8"	KD, KA 101,103,107,915 KA 51001,51002,51003,51004 <sup>*note</sup> Custom keyed	
200B	Drawer	26D, 10B	1-5/8"		
Key-retaining:		Specify item <b>200BKI</b> for inverted drawers and <b>200BKV</b> for vertical drawers. ( <b>BKI</b> and B <b>KV</b> designations are <i>only required for key retaining locks</i> ).			
Long bolt:		Specify LB for long bolt installed in lock.			

## 200M - MRI Function (Non-Magnetic)

Item	Function	Finish	Cyl. Length	Keying	
200M	Drawer	26D	15/16", 1-3/8" or 1-5/8"	KD, KA 101,103,107,915 KA 51001,51002,51003,51004* <sup>note</sup> Custom keyed	
Key-retaining (MRI):		Specify item <b>200MKI</b> for inverted drawers and <b>200MKV</b> for vertical drawers. ( <b>MKI</b> and <b>MKV</b> designations are <i>only required for key retaining MRI locks</i> ).			
Long bolt:		Specify LB for long bolt installed in lock.			

<sup>\*note</sup> KA# 51001, 51002, 51003 and 51004 available in US26D finish only





# SPECIFICATIONS

- Keying: Can be keyed together with other N Series locks
- Rekeyable: Easily rekeyable via set screw cylinder release mechanism
- ANSI/BHMA: Passed ANSI/BHMA A156.11 Grade 1 performance requirements. Equivalent to E07121(100DR) / E07041(200DW).
- Standard function: Key removable in locked or unlocked position. Standard function locks are non-handed.
- Key-retaining: Key removable in locked position only. Specify handing (KL/KR for doors or KI/KV for drawers) when ordering.

US Patent Nos: 4,899,563; 4,920,774

Body: Zinc die cast

Cylinder: Solid brass, pin tumbler Cylinder length: 15/16", 1-3/8" or 1-5/8"

Barrel diameter: 7/8" Finish: 26D, US4, 10B or US19 Packaged: Packed 10 per box

## **KEYING INFORMATION**

Keyway: N Series (equivalent to National D4291 4-pin or D4292 5-pin system)
Keys: Includes 2 keys per lock
Stock keying: KD/KA - 4 pin standard
Stock KA#: 101, 103, 107, 915, 51001, 51002, 51003, 51004\*note
Masterkeyed: 5 pin standard

- Grand masterkeyed: Available
- Keyblank 4-pin: KBN-4-NP (equivalent to NA14, 1069L) Keyblank 5-pin: KBN-5-NP
- equivalent to NA12, 1069LA)
- Keyblank 5-pin copper plated: KBN-5B (use with 100M/200M MRI locks)

## **INCLUDED ACCESSORIES**

- 200DW/200B: 2 keys, 12-3 angle strike, and lock mounting screws
- **200M:** 2 keys, 56-1 bar strike, and lock mounting screws (keys, components and materials are non-ferrous/non-magnetic)

## **OPTIONAL ACCESSORIES**

See the accessories section of this catalog for a complete list.

Spacers: WP20 (3/16" thick), WP21 (3/32" thick), WP22 (1/4" thick), WP23 (1/2" thick)

Strikes: 07S, 12-1, 12-2, 12-3, 12-5, 12-4, 56-1 Trim ring: TR1256

Through-bolt hardware: ETS2 trim plate, ETS2-PL trim pull and ETST2 template

Long bolt (bolt only): 15-1-35 for use with 200DW/200B/200M locks