
► 600DW | 600B | 600M Drawer Lock



ANSI/BHMA A156.11 Grade 1 E07041

Woodwork Institute (WI) acknowledged product



600DW

Function: Standard function lock Includes: 2 keys, 12-3 bar strike, and lock mounting screws

600B - Weather Resistant

Function: Weather resistant construction. Suitable for outdoor use in covered areas only. Includes: 2 keys, 12-3 bar strike, and lock mounting screws

600M - MRI Function

Function: MRI locks are made of all non-magnetic materials and components specifically for use in MRI medical applications.

Includes: 2 keys, 56-1 bar strike, and lock mounting screws (keys, components and materials are non-ferrous/non-magnetic)

600DW

Item	Function	Finish	Cyl. Length	Keying	
600DW	Drawer	26D, US4, 10B	15/16" or 1-3/8"	KD, KA 4T21579, 4T37526 Custom Keyed	
Key-retaining:		Specify item 600KI for inverted drawers and 600KV for vertical drawers. (KI and KV designations are <i>only required for key retaining locks</i>).			
Long bolt:		Specify LB for long bolt installed in lock.			

600B - B Series (Weather Resistant)

Item	Function	Finish	Cyl. Length	Keying	
600B	Drawer	26D, US4, 10B	15/16" or 1-3/8"	KD, KA 4T21579, 4T37526 Custom Keyed	
Key-retaining:		Specify item 600BKI for inverted drawers and 600BKV for vertical drawers. (BKI and BKV designations are only required for key retaining locks).			
Long bolt:		Specify LB for long bolt installed in lock.			

600M - MRI Function (Non-Magnetic)

Item	Function	Finish	Cyl. Length	Keying	
600M	Drawer	26D	15/16" or 1-3/8"	KD, KA 4T21579, 4T37526 Custom Keyed	
Key-retaining (MRI):		Specify item 600MKI for inverted drawers and 600MKV for vertical drawers. (MKI and MKV designations are <i>only required for key retaining MRI locks</i>).			
Long bolt:		Specify LB for long bolt installed in lock.			

SPECIFICATIONS

Keying: Can be keyed together with other R Series locks

Rekeyable: Easily rekeyable via set screw cylinder release mechanism

ANSI/BHMA: Passed ANSI/BHMA A156.11 Grade 1 performance requirements. Equivalent to E07121(500DR) / E07041(600DW).

Standard function: Key removable in locked or unlocked position. Standard function locks are non-handed.

Key-retaining: Key removable in locked position only. Specify handing (KL/KR for doors or KI/KV for drawers) when ordering.

US Patent Nos: 4,899,563; 4,920,774

Body: Zinc die cast

Cylinder: Solid brass, pin tumbler Cylinder length: 15/16" or 1-3/8"

Barrel diameter: 7/8" Finish: 26D, US4 or 10B Packaged: Packed 10 per box

KEYING INFORMATION

Keyway: R Series (equivalent to CCL R1 system)

Keys: Includes 2 keys per lock Stock keying: KD/KA - 5 pin standard Stock KA#: 4T21579, 4T37526

Masterkeyed: 5 pin standard, 6 pin available

Grand masterkeved: Available Keyblank 5-pin: KBR-5-NP (equivalent to CO106, 1003A) Keyblank 5-pin copper plated: KBR-5B (use with M Series MRI locks)

Keyblank 6-pin: KBR-6-NP (equivalent to L1003A)

INCLUDED ACCESSORIES

600DW/600B: 2 keys, 12-3 angle strike, and lock mounting screws

600M: 2 keys, 56-1 bar strike, and lock mounting screws (keys, components and materials are nonferrous/non-magnetic)

OPTIONAL ACCESSORIES

See the accessories section of this catalog for a complete list.

Spacers: WP20 (3/16" thick), WP21 (3/32" thick), WP22 (1/4" thick), WP23 (1/2" thick) Strikes: 07S, 12-1, 12-2, 12-3, 12-4, 56-1 strikes

Trim ring: TR1256

Through-bolt hardware: ETS2 trim plate, ETS2-PL

trim pull and ETST2 template

Long bolt (bolt only): 15-1-35 for use with

600DW/600B/600M locks