

ARCHITECTURAL SPECIFICATIONS

Olympus Lock Institutional Grade Cabinet Locks

R SERIES: CCL R1 Keyway

5 PIN — Up to 2,000 key changes available under a master key system

6 PIN — Up to 4,000 key changes available under a master key system

OLYMPUS DEADBOLT LOCKS — *Olympus 500DR (door) / Olympus 600DW (drawer)*

Cabinet locks: Provide Olympus 500DR (door) and Olympus 600DW (drawer) easily rekeyable cabinet locks such as manufactured by Olympus Lock, Inc. All locks to include: working cylinder slides, .095 diameter pins and forwardly removable cylinders for rekeying without totally disassembling lock body. Furnish 2 keys per lock and bar or slotted strikes as required. Spacers to be provided as required for flush fit with outside face of casework material. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

OLYMPUS LATCH LOCKS — *Olympus 997R (RH-door) / 997L (LH-door)* — *Olympus 996 (DW-drawer)*

Cabinet locks: Provide Olympus 997 (door) and 996 (drawer) easily rekeyable latch locks such as manufactured by Olympus Lock, Inc. All locks to include: working cylinder slides, .095 diameter pins, forwardly removable cylinders for rekeying without totally disassembling lock body and four-way reversible handing. Keyway will remain in the vertical position regardless of installation as a door or drawer. Spacers will be provided as required for flush fit with outside face of casework material. Furnish 2 keys per lock and lipped strike as required. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

OLYMPUS SLIDING DOOR LOCK — *Olympus 400SD (sliding door/plunger)*

Cabinet locks: Provide Olympus 400SD (sliding door/plunger) lock. Locks shall be easily rekeyable without removal from cabinet via a speed release mechanism such as manufactured by Olympus Lock, Inc. All locks to include: working cylinder slides, .095 diameter pins, forwardly removable cylinders for rekeying without totally disassembling lock body, built in bolt extension and strike locator. Locks will include 2 keys per lock and shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

OLYMPUS SHOWCASE RATCHET LOCK — *Olympus 429R (showcase/ratchet)*

Ratchet locks: Provide Olympus 429R (showcase/ratchet) lock. Locks shall be easily rekeyable via a speed release mechanism such as manufactured by Olympus Lock, Inc. All locks to include: working cylinder slides, .095 diameter pins, and forwardly removable cylinders for rekeying without totally disassembling lock body. Locks will include 2 keys per lock and shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

OLYMPUS CAM LOCKS — *Olympus DCR1, DCR2, DCR3, DCR4 (cam lock)*

Cabinet locks: Provide Olympus DCR Series (cam lock). Cam locks to be easily rekeyable and field reversible such as manufactured by Olympus Lock, Inc. All cylinders to include .095 diameter pins, a working top slide mechanism and retainer staple to permit easy rekeying and field maintenance of lock. Cam locks will have a 1 inch face diameter and include an anti-rotation plate to trap the hex nut and prevent the lock from twisting in the hole. All cam locks will be field reversible such that one straight and one offset cam will provide all locking positions. Locks will include 2 keys per lock and shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

Phone: 206-362-3290
Fax: 206-362-3569
www.olympuslock.com



ARCHITECTURAL SPECIFICATIONS

R Series: CCL R1 Keyway

OLYMPUS DEADBOLT LOCKS — *Olympus R078 (drawer)*

Cabinet locks: Provide R078 (drawer) easily rekeyable cabinet locks such as manufactured by Olympus Lock, Inc. All locks to include: .095 diameter pins, working cylinder slides and forwardly removable cylinders for rekeying without totally disassembling lock body. Provide spacers as required for flush fit with outside face of casework material. Locks will include 2 keys per lock and shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

MANUFACTURER: Olympus Lock, Inc., Lynnwood, WA, www.olympuslock.com

Contact: (phone) 206-362-3290, (email) info@olympuslock.com.

GENERAL SPECIFICATIONS

All cabinet door, drawer, and sliding door locks shall be easily rekeyable such as manufactured by Olympus Lock, Inc. All locks will provide .095 diameter pins, a set screw cylinder release system (US Patent 4,899,563) or speed-release cylinder removal system (US Patent 5,121,619) so easy access to the cylinder and cylinder housing can be gained by facility or locksmith personnel for servicing and rekeying. Only a similar patented system that provides working top slides for easy access to top springs and pins is acceptable. No crimping on top slides will be considered. Cylinder spacers will be provided to allow flush fit of lock cylinders on outside of cabinet material. All cam lock cylinders to include a working top slide mechanism and retainer staple to permit easy rekeying and maintenance of lock (US Patent 5,038,589). All cam locks will have a 1 inch face diameter and include an anti-rotation plate to trap the hex nut and prevent the lock from twisting in the hole. All cam locks to be field reversible such that one straight and one offset cam will provide all locking positions (US Patent 5,737,950). Finishes will be similar to BHMA standards for US3, US4, US26D and US10B. No painted finishes will be acceptable.

Note: Rekeyable cabinet locks must be capable of being rekeyed in 5 minutes or less when off the cabinet to qualify under this specification.

Phone: 206-362-3290
Fax: 206-362-3569
www.olympuslock.com



**OLYMPUS
LOCK**_{U.S.}

Institutional grade cabinet locks.