ARCHITECTURAL SPECIFICATIONS

Olympus Lock Institutional Grade Cabinet Locks

STANDARD CYLINDER: Schlage C Keyway

5 PIN — Up to 2,000 key changes available under a master key system **6 PIN** — Up to 4,000 key changes available under a master key system

OLYMPUS DEADBOLT LOCKS — Olympus 700S (door) / Olympus 800S (drawer)

Cabinet locks: Provide Olympus 700SC (door) and Olympus 800SC (drawer) easily rekeyable cabinet locks such as manufactured by Olympus Lock, Inc. All locks to include: forwardly removable cylinders for rekeying without totally disassembling lock body. Furnish 2 keys per lock and bar or slotted strikes as required. Spacers to be provided as required for flush fit with outside face of casework material. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

OLYMPUS LATCH LOCKS — Olympus L78R (RH-door) / L78L (LH-door) — Olympus L78V (DW-drawer)

Cabinet locks: Provide Olympus L78L/L78R (door) and Olympus L78V (drawer) latch locks. Locks shall be easily rekeyable such as manufactured by Olympus Lock, Inc. All latch locks to provide: forwardly removable cylinders for rekeying without totally disassembling lock body. Locks shall provide for field reversible handings such that keyway will remain in the vertical position regardless of installation as a door or a drawer. Spacers to be provided for flush fit with outside face of casework material. Furnish 2 keys per lock and strikes as required. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

OLYMPUS DEADLATCHING LOCK — *Olympus 850S (DW-drawer)*

Cabinet locks: Provide Olympus 850SC (drawer) lock. Locks shall be easily rekeyable such as manufactured by Olympus Lock, Inc. All drawer latch locks to provide a deadlocking function, forwardly removable cylinders for rekeying without totally disassembling lock body, and spacers as required for flush fit with outside face of casework material. Furnish 2 keys per lock and strikes as required. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

OLYMPUS SHOWCASE RATCHET LOCK — Olympus 829R (showcase/ratchet)

Cabinet locks: Provide Olympus 829R sliding door (showcase/ratchet) lock such as manufactured by Olympus Lock, Inc. All locks will include easily removable cylinders for rekeying. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule. Furnish 2 keys per lock.

OLYMPUS CAM LOCKS — Olympus 820SC (cam lock)

Cabinet locks: Provide Olympus 820SC (cam lock) locks. Locks shall be easily rekeyable such as manufactured by Olympus Lock, Inc. All locks will include easily removable cylinders for rekeying without totally disassembling lock body. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule. Furnish 2 keys per lock.



ARCHITECTURAL SPECIFICATIONS

Standard Cylinder: Schlage C Keyway

MANUFACTURER: Olympus Lock, Inc., Lynnwood, WA, www.olympuslock.com Contact: (phone) 206-362-3290, (email) info@olympuslock.com.

GENERAL SPECIFICATIONS

All cabinet door, drawer, and sliding door locks shall be easily rekeyable such as manufactured by Olympus Lock, Inc. All locks will provide a set screw cylinder release system (US Patent 4,899,563) so easy access to the solid brass cylinder and cylinder housing can be gained by facility or locksmith personnel for servicing and rekeying. Only a similar patented system that provides working top slides for easy access to top springs and pins is acceptable. No crimping on top slides will be considered. Cylinder spacers will be provided to allow flush fit of lock cylinders on outside of cabinet material. Finishes will be similar to BHMA standards for US3, US26D, and 10B. No painted finishes will be acceptable.

Note: Rekeyable cabinet locks must be capable of being rekeyed in 5 minutes or less when off the cabinet to qualify under this specification.

Phone: 206-362-3290 Fax: 206-362-3569 www.olympuslock.com

