PRODUCT DATA SHEET

722S | 722S-TBM

SFIC: Sliding Door **Plunger Lock**



SPECIFICATIONS

Retrofits: Best 2S, 2S-TBM Standard function: Key removable in locked and unlocked position. Key-retaining function: Key removable in locked position only. Specify -*KR* for key-retaining. TBM function: Specify TBM for "through-bolt mounting" Body: Solid brass Barrel length: 1-3/4" Bolt throw: 1/2" Max. door thickness: 1-7/8" Min. door thickness (TBM): 5/8" Finish: 26D Packaged: Packed 10 per box

KEYING INFORMATION

Cores: Not included Accepts: Best, Arrow, Falcon, KSP, Schlage SFIC or equivalent small format interchangeable cores Compatible electronic cylinders: Medeco Nexgen XT or VIDEX CyberLock SFIC cylinders

INCLUDED ACCESSORIES

725-1 spacer to fit 6 or 7 pin cores Matching strike 725-PA plastic thumbturn TBM locks include through-bolt plates and screws

OPTIONAL ACCESSORIES

SFIC cores: 206/207 Series



722S

Function: Sliding door plunger lock for bypassing sliding doors

- Material: Fits up to 1-3/4" material
- Standard function: Key removable in locked or unlocked position. Standard locks are non-handed.
- Key-retaining function: Key removable in locked position only. Specify -KR for key-retaining.



722S-TBM

- Function: Sliding door plunger lock for bypassing sliding doors. Includes with through-bolt mounting hardware.
- Material: Fits up to 1-3/4" material
- Standard function: Key removable in locked or unlocked position. Standard locks are non-handed.
- Key-retaining function: Key removable in locked position only. Specify -KR for key-retaining.



WARNING: This product can expose you to chemicals including chromium, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



722S 722S-TBM SFIC: Sliding Door Plunger Lock

OPTIONAL ACCESSORIES - See our website for a complete list of optional components.

206/207 Series


- 206 Series 6-pin SFIC cylinder
- 207 Series 7-pin SFIC cylinder




BEST compatible

interchangeable core cylinders









722S-TBM Unlocked

Through-bolt mount





DIMENSIONS

Through-bolt mount

