DCN SERIES

N Series: 3/4" Barrel Diameter Grade 1 Cam Lock

SPECIFICATIONS

Keying: Can be keyed together with other N Series locks

Cylinder length: Four sizes available (see table with dimensions on page 2)

Rekeyable: Easily rekeyable via cylinder retainer clip ANSI/BHMA: Passed ANSI/BHMA A156.11

Grade 1 performance requirements. Equivalent to E07261 / E07271.

US Patent Nos: 5,038,589; 5,737,950

Body: Zinc die cast

Cylinder: Zinc die cast, pin tumbler

- Standard function: Key removable in locked or unlocked position.
- Key retaining function: Alternate key-retaining shifters are available separately for key removable in locked position only.

Cams: 2 reversible cams work in all positions

Face: 1" face covers splintering, no additional trim ring required Finish: 26D, US3, 10B or US19 Packaged: Packed 10 per box

KEYING INFORMATION

Keyway: N Series (equivalent to National D4291 4-pin or D4292 5-pin system) Keys: Includes 2 keys per lock Stock keying: KD/KA - 4 pin standard Stock KA#: 101, 103, 107, 915, 51001, 51002, 51003, 51004 Masterkeyed: 5 pin standard Grand masterkeyed: Available Keyblank 4-pin: KBN-4-NP

(equivalent to NA14, 1069L) Keyblank 5-pin: KBN-5-NP (equivalent to NA12, 1069LA)

INCLUDED ACCESSORIES

Straight cam #DCNP-100-SC Offset cam #DCNP-100-BC Anti-rotation plate #DCNP-500-ARP

OPTIONAL ACCESSORIES

See page 2.

DCN

Keyway: N Series, National Keyway Handing: Includes 2 cams that work in all handings (door or drawer)


DCN SERIES FEATURES

- Non-handed—Field reversible locking positions: right-hand, lefthand, vertical and inverted
- Only 2 cams required—Ships with reversible straight and offset cams that meet requirements of all locking positions
- Easy rekeyability—Allows for a quick installation and increased productivity

ANSI/BHMA Grade 1

Woodwork Institute (WI) acknowledged product

E07261 | E07271



AVAILABLE FINISHES







5/16"


11/16"

US26D


US10B US19

0

INCLUDED CAMS



straight cam







WARNING: This product can expose you to chemicals including chromium, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

DCN SERIES N Series: 3/4" Barrel Diameter Grade 1 Cam Lock

ANSI/BHMA Grade 1 E07261 | E07271 Woodwork Institute (WI) acknowledged product

OPTIONAL ACCESSORIES - See our website for a complete list of optional components.

Other Accessories

Key-retaining cam shifters

- For door function: DCNP-200-KDR
- For Drawer function: DCNP-200-KR Washers
- Pronged wood washer: DCNP-SPW •
- Self-adhesive clear plastic washer for mounting lock on glass: DCNP-GW

Finger Pull

• Finger pull: DCNP-300-FP

TRB7 Series Trim Collars

Finish: US26D





TRB7-14-26D Spacer collar, 1/4



TRB7-12-26D Spacer collar, 1/2




Optional Cams

Note: Offset cams are reversible and can be used in either the inbent or outbent position.

ltem	Description / Packed Each	Item	Description / Packed Each	
DCNP-HD-875	7/8" long straight cam	DCNP-100-BC	1-1/4" long cam, 5/16" offset	
DCNP-HD-1 DCNP-100-SC	1" long straight cam 1-1/4" long straight cam	DCNP-100-BC5 DCNP-100-HC1	1-1/4" long cam, 1/2" offset 1-1/2" long hook cam, 5/16" offset	
DCNP-100-SC2	1-3/4" long straight cam	DCNP-100-HD	1-7/16" long cam, 1/2" offset	
DCNP-100-SC3	1-1/2" long straight cam	DCNP-100-HD2	1-3/4" long cam, 5/16" offset	
DCNP-100-LC	3" long straight cam	DCNP-100-HD3	1-1/8" long cam, 5/16" offset	
ltem	Description / Packed Each	DCNP-100-LBC	1-1/2 long cam, 5/16" offset	
DCNP-100-B1	Straight cam with oval cutout	> Visit our website www.olympuslock.com for condimension and descriptions of available optional cams.		
DCNP-100-B2 DCNP-100-B3	U-shaped cam Straight hook cam			


DIMENSIONS | TYPICAL INSTALLATION




DIMENSIONS

	For Mat. Thickness	Straight Cam (X)	Inbent Cam (Y)	Outbent Cam (Z)	Cylinder Length (A)
DCN1	3/4"	1-1/16"	3/4"	1-3/8"	1"
DCN2	7/8"	1-3/16"	7/8"	1-1/2"	1-1/8"
DCN3	1-1/8"	1-7/16"	1-1/8"	1-3/4"	1-3/8"
DCN4	1-1/2"	1-13/16"	1-1/2"	2-1/8"	1-3/4"

MOUNTING CUTOUT











DCNP-300-FP

mounting lock on glass